

SC - MAT (BC&SC™)

The Unique Concrete & Stone Sealer by Scanmaskin

Chemical description

SC - Mat is a patented, satin, stain and wear resistant finish for improving the sheen, hardness and chemical resistance of natural and cast stone, terrazzo, masonry, and other cement-based surfaces.

Mode of action

Ideal for ground and polished concrete surfaces as well as integrally colored, dyed and/or stained concrete. **SC - Mat** enhances the color intensity of natural and cast stone, and integrally colored, dyed, or acid stained decorative concrete. It also reduces efflorescence and mineral deposits making treated surfaces shinier and more attractive.

Properties

- Delivers rapid shine development with increased abrasion and stain resistance
- Keeps dirt and contaminants from penetrating, making cleaning faster, more effective and more economical
- Ready to use in a few hours—rapidly cures into a durable finish for facilities that require maximum protection and little-to-no downtime
- Forms a protective “micro-surface layer” that is breathable, dense, abrasion resistant, and that will not peel or flake
- Reduces maintenance, cleaning costs and costly repairs—simply damp mop or machine scrub

Any technical application recommendations, verbal or in writing, provided by us in good faith to our customers/users for their assistance and on the basis of our experience and present state of knowledge are absolutely noncommittal. This also applies to any existing industrial property rights or foreign statutory provisions. Any recommendation of ours can therefore not be regarded as a legal relationship or contractual commitment, nor does it establish any sales contract deed of covenant. It is the buyer's responsibility to examine the suitability of our products for their intended application.

Scanmaskin Sweden AB (Headoffice)

Heljesvägen 10 — SE-437 36 Lindome — Box 187 — SE-437 22 Lindome — Phone: +46-31 99 71 97

WWW.SCANMASKIN.COM

Note

Before application, always do a small test sample in a less-visible area to be sure there are no variables or contaminants in the substrate that may be incompatible with this product.

Application

- 1st coat: 37 -74 sq. m/L
- 2nd and subsequent coats: 74 – 98 sq. m/L
- Texture and absorption of surface will determine final coverage rates. Porous concrete surfaces may require additional material.

Properties

- Active Ingredients: 100% of total solids
- Specific Gravity: 1.09
- pH: 11.5
- V.O.C Content: <50g/L
- Flash Point: N/A
- Freeze Point: 0°C

Storage

SC - Mat must be protected from frost and must not be stored in plastic containers. The shelf life is at least 6 months in unopened factory sealed containers.

Labelling / Safety

Please see safety data sheet.

Packaging

Can
Drum
Container

09/2019

SCANMASKIN
MACHINES-MINERALS-KNOW-HOW

Scanmaskin Sweden AB (Headoffice)

Heljesvägen 10 – SE-437 36 Lindome – Box 187 – SE-437 22 Lindome – Phone: +46-31 99 71 97

WWW.SCANMASKIN.COM